




## CDIP Wave Observations During Hurricane Matthew

**US Army Corps** of Engineers®

Hs values from NOAA's Operational Wave Watch III output vs. Hs values computed from the station buoy

Mean slope was computed by least squares linear regression for each storm-centered quadrant (i.e.

quadrant 1 is NE of the storm eye, increasing clockwise), for storm eye locations within 8 degrees of arc



weakened below Category 1 Hurricane threshold. For all three

passage of the storm, actual Hs values were typically at leas


Figure 4. Scatter plots of Hs values from WaveWatch III hindcast


vs. buoy data analysis for stations north of Cape Hatteras,

separated by quadrant of station location relative to hurricane

eye location. Mean slope for each quadrant is indicated.

James Behrens, Eric Terrill, Julianna Thomas, David Castel, Richard Seymour, Robert E. Jensen<sup>1</sup> Scripps Institution of Oceanography, US Army Corps of Engineers<sup>1</sup> jb@cdip.ucsd.edu





• Established 1975 • Primary funding comes from the U.S. Army Corps of Engineers (USACE).

• CDIP is a wave monitoring network along United States coastlines.

Coastal Data Information Program (CDIP)

- Several sites analyzed here are cost shared with the U.S. Navy and National Oceanic Atmospheric Administration's U.S. Integrated Ocean Observing System (NOAA IOOS), and the US Navy.
- Datawell Waverider moored directional wave buoys are the wave sensors.
- Sensitive to wave motion period range 2 sec < T < 30 sec
- Waveriders report their continuous wave observations in 27 minute segments.
- Data telemetry is via Iridium.

**Hindcast Comparison** 

during the storm's approach (g4) but

Figure 3. Scatter plots of Hs values from WaveWatch III hindcast

vs. buoy data analysis for stations south of Cape Hatteras,

separated by quadrant of station location relative to hurricane

eye location. Mean slope for each quadrant is indicated.

(~900 km) of each station.

data record centered within 30 minutes following each hindcast.

- Data quality control is applied prior to dissemination to NOAA/NDBC/NWS.
- These data streams are converted into a variety of standardized data products by CDIP at the Scripps Institution of Oceanography, University of California, San Diego, and are available in near-real time.
- At present, CDIP's network consists of ~70 buoys.

cdip.ucsd.edu

7.0

7.8

7.0

3.57

3.87

3.19

6.2 3.02

11.76

7.14

6.25

9.09

139

019 4.64

035 -1.46

064 2.26

-0.07

1.67

1.78

1.69

1.82

17

26

48

5.97

6.88

5.40

5.51

09-22

10-11

**UTC**: Universal Coordinated Time day and hour of Hmax arrival, October 2016

**Dp**: Peak direction corresponding to the measured Hs (meteorological convention)

**Delay**: Time elapsed between Hs max and Hmax; Delay > 0 means Hmax occurred after Hs max

Hmax: Amplitude (trough-to-crest) of largest recorded individual wave

Hmax / Hs: Ratio of Hmax to Hs during the time interval of Hmax arrival

**Hs**: Significant wave height at time of Hmax arrival

**Tp**: Peak period corresponding to the measured Hs

**Depth**: Water depth at buoy station

Wallops Island, VA

Jeffrey's Ledge, NH

Barnegat, NJ

Block Island, RI

